## **SPABRITE®**

## INCANDESCENT LIGHTS FOR SWIMMING POOLS AND SPAS

## **Featured Highlights**

- · Stainless steel face rings
- · Prismatic tempered glass lens
- · Stainless steel housing
- · Easy service stainless steel clamp
- Incandescent 12V and Halogen 120V lamp
- · Low water cutoff
- · Easy to service
- Plastic snap-on colored face ring covers available

SpaBrite lights are available with stainless steel face rings. These lights are perfect for spas and areas where space is not available for a full-size light. SpaBrite lights install in small plastic or stainless steel Pentair niches.

#### CALIFORNIA PROPOSITION 65 WARNING

▲ WARNING: Cancer and Reproductive Harm.
▲ AVERTISSEMENT: Peut Causer le Cancer et des Dommages au Système Reproducteur.
▲ ADVERTENCIA: Cáncer y Daño Reproductivo.

www.p65warnings.ca.gov.

## TRADEGRADE



SpaBrite Incandescent Lights

### **Ordering Information**

					-				
Product	Voltage	Wattage	Cord Length (Ft.)	Carton Oty.	Carton Wt. (Lbs.)				
	SPABRITE	HALOGEN LIGHTS WITH S	TAINLESS STEEL FACE	E RING – 120 VOLT					
78106000	120	60W (100W equivalency)	30	1	7				
78106100	120	60W (100W equivalency)	50	1	9				
78106200	120	60W (100W equivalency)	100	1	14				
78106300	120	60W (100W equivalency)	150	1	19				
78106400	120	60W (100W equivalency)	200	1	24				
SPABRITE LIGHTS WITH STAINLESS STEEL FACE RING – 12 VOLT									
78101200	12	100W	15	1	6				
78108200	12	100W	50	1	9				
78107500	12	100W	100	1	14				
SPABRITE WITH STAINLESS STEEL FACE RING - CANADIAN LIGHTS									
78103202	12	100W equivalency	30	12	9				
78106002	120	60W (100 equivalency)	30	12	9				
		ACCES	SSORIES						
79212200	Snap-on face ring, plastic, white			1	1/2				
79212211	Snap-on face	ring plastic, black	1	1/2					
79212265	Snap-on face ring, plastic, gray			1	1/2				
79108900	Snap-on color	lens plastic, red	1	1/2					
79109000	Snap-on color	lens plastic, blue	1	1/2					
650019	Snap-on color	lens kit (magenta, purple, teal	1	2					


All Pentair UL Listed underwater lights are certified for use in fresh water with up to 6,000 ppm salinity.

Note: All 120 volt pool and spa lights must be connected to a branch circuit protected by a ground fault circuit interrupter (GFCI).

Note: All cord lengths over 50 feet on 12 volt lights create resistance that dramatically reduces the light output. This condition exists on all low voltage lights regardless of design or manufacturer.

Notice: Underwriters Laboratories has listed Pentair Water Pool and Spa, Inc. lights for use with Pentair Water Pool and Spa, Pentair Pool Products, American Products, Purex, or PacFab niches ONLY. To ensure proper grounding/bonding connections install only Pentair Water Pool and Spa lights in Pentair, Water Pool and Spa, Pentair Pool Products, American Products, Purex or PacFab niches only.

#### **Dimensions and Certic cations**







## **AQUALIGHT®**

# HALOGEN QUARTZ LIGHTS WITH STAINLESS STEEL FACE RING

## **TRADE**GRADE



AquaLight Halogen Lights

The AquaLight light uses halogen quartz bulbs and designed for installation in small plastic or stainless steel Pentair niches. The light shell is high-quality stainless steel and the lens is Prismatic tempered glass.

CALIFORNIA PROPOSITION 65 WARNING

▲ WARNING: Cancer and Reproductive Harm.
 ▲ AVERTISSEMENT: Peut Causer le Cancer
 ◆ des Dommages au Système Reproducteur.
 ▲ ADVERTENCIA: Câncer y Daño Reproductivo.
   www.p65warnings.ca.gov.


### **Featured Highlights**


- · Prismatic tempered glass lens
- · Stainless steel housing
- · Easy service stainless steel clamp
- · Halogen-quartz lamp
- · Low water cutoff
- · Easy to service
- Plastic snap-on face rings and colored lenses available

### **Ordering Information**

aering iiii	Offication				
Product	Voltage	Wattage	Cord Length (Ft.)	Carton Oty.	Carton Wt. (Lbs.)
	,	AQUALIGHT LIGHT:	S – 100 WATT, 120 VOLT		
77111100	120	100	15	1	6
77118100	120	100	50	1	9
77310100	120	100	100	1	14
	,	AQUALIGHT LIGHTS	S – 250 WATT, 120 VOLT		
77161100	120	250	15	1	6
77168100	120	250	50	1	9
77360300	120	250	100	1	14
77365000	120	250	150	1	19
77362000	120	250	200	1	24
		AQUALIGHT LIGH	TS – 75 WATT, 12 VOLT		
77181100	12	75	15	1	6
77188100	12	75	50	1	9
77182500	12	75	100	1	12
		AQUALIGHT LIGHT	S - CANADIAN LIGHTS		
77113102	120	100	30	12	9
77163102	120	250	30	23	9
		ACCE	SSORIES		
79212200	Snap-on face ring, pl	astic, white	1	.5	
79212211	Snap-on face ring pla	astic, black	1	.5	
79212265	Snap-on face ring, pl	astic, gray	1	.5	
79108900	Snap-on color lens p	lastic, red	1	.5	
79109000	Snap-on color lens p	lastic, blue	1	.5	
650019	Snap-on color lens k	it (magenta, purple, te	1	2	

### **Dimensions and Certi cations**









All Pentair UL Listed underwater lights are certified for use in fresh water with up to  $6,\!000$  ppm salinity.

Note: All 120 volt pool and spa lights must be connected to a branch circuit protected by a ground fault circuit interrupter (GFCI).

Note: All cord lengths over 50 feet on 12 volt lights create resistance that dramatically reduces the light output. This condition exists on all low voltage lights regardless of design or manufacturer.

Notice: Underwriters Laboratories has listed Pentair Water Pool and Spa, Inc. lights for use with Pentair Water Pool and Spa, Pentair Pool Products, American Products, Purex, or PacFab niches ONLY. To ensure proper grounding/bonding connections install only Pentair Water Pool and Spa lights in Pentair, Water Pool and Spa, Pentair Pool Products, American Products, Purex or PacFab niches only.