
### **Specifications**

Opcomodiono	
Model Number	PRO100
Nominal Heating Capacity	97KW (331,000 BTU)
Test Lab (26/26/80)	97KW (331,000 BTU)
Test lab (15/26/70)	67 kW (229,000 BTU)
Test Lab (10/26/63)	58 kW (198,000 BTU)
Compressor (HP)	(2 x) 11HP
Manufacturer	Sanyo
Compressor number	C-SCP360H38A
Water Flow & Plumbing Characteristics	
Water Bypass Type	Ext. Field Install
Min./Max. Water Flow Rate (LPM)	500-680
Min./Max. Water Inlet Temperature (°C)	14° - 40°
Plumbing Connection Size (Slip)	80mm / 3" PVC
Electrical Characteristics	
50Hz Dual Rated Supply Voltage (VAC)	380-415V
Supply Voltage Phase	3
Unit run current (AMP)	29.5
Power consumption (kW)	16.12
Coefficient of Performance @ 26/26/80 (COP)*	6.4
Min./Max. Air Inlet Temperature (°C)	6° / 40°
Refrigerant Characteristics	
Refrigerant Type	R-410A
Physical Characteristics	
Cabinet Construction	Powder coat sheet metal
Color	Black
Weight (kg.)	453
Dimensions (mm)	1730W-1090L –1120H
Noise Emission Characteristics	
Noise Emission (dBA)	69 @ 1metre & 59 @ 3 metres

<sup>\* (26/26/60) =</sup> Air Temp: 26° / Water Temp 26° / Humidity 60%

### **Dimensions**



#### Clearance



WA - Perth Tel: +61 8 9273 1900

SA/NT - Adelaide Tel: +61 8 8244 6000

ACT Distribution Tel: +61 2 6280 6476

l: +1 450 748 1421

Waterco (Far East) Sdn Bhd Jakarta, Indonesia Tel: +62 21 4585 1481 Waterco Singapore Intl Pte Ltd Nehsons Building, Singapore Tel: +65 6344 2378 aterco (NZ) Limited uckland, New Zealand d: +64 9 525 7570

DISTRIBUTED BY:












The new generation Electroheat PRO heat pump is the latest advancement in commercial size swimming pool heating. The PRO 100 has been designed to deliver efficient cost effective large pool heating in an easy to operate and install package.

- Electronically controlled temperature management
- Fault diagnostic system and inbuilt protection devices
- Hermetic scroll compressors
- Titanium heat exchangers
- R410A Refrigerant




www.waterco.com





## Fans

- Twin 660mm fans for maximum airflow
- Low noise emissions 69dBA @ 1 metre



### **Evaporators**

- Twin evaporators for enhanced heat absorption
- Automatic hot gas de-icing for cold climates




Compressor
Twin high performance
11HP Sanyo hermetic
scroll compressors



### ✓ Cost Effective Heating

✓ Save up to 50% over natural gas, 80% over propane gas and 500% over electric element pool heater running costs compared to heat pumps.

## **Electroheat Pro 100 Temperature Rise**



Testing performed on 100,000L water volume 12/2012

### **Control Panel**


- Electronically controlled temperature management
- Continuous digital temperature display
- Phase and compressor monitoring





# **Heat Exchangers**

Six titanium coiled exchangers for maximum heat transfer and protection against corrosion




### **Water Connection**

- Easy to connect single in/out 80mm (3") water connections.
- Integral flow switch protecting equipment from operation when no flow is detected



Electrical Connections
Easy cable entry and
electrical connection access



### Cabinet

- Made from heavy duty powder coat sheet metal
- Easy installation and relocation with allowance for forklift tynes

